

Enquiry please quote     Order please process

Date \_\_\_\_\_

**Contact Details**

Ordered by \_\_\_\_\_  
 Company Name \_\_\_\_\_  
 Address \_\_\_\_\_  
 \_\_\_\_\_ Postcode \_\_\_\_\_  
 Telephone \_\_\_\_\_  
 Fax \_\_\_\_\_  
 Email \_\_\_\_\_  
 Order No. \_\_\_\_\_ Your Reference \_\_\_\_\_  
 Delivery Date Requested \_\_\_\_\_

**Dual Colours**

RAL 7016 Anthracite Grey Matt Outside / RAL 9910 Hippca Gloss White Inside

*Note: Other single and dual colours available on request.*

Marine Grade Paint Required     Yes     No

**Site Contact**

Contact Name \_\_\_\_\_  
 Delivery Address \_\_\_\_\_  
 \_\_\_\_\_ Postcode \_\_\_\_\_  
 Telephone \_\_\_\_\_

**Cill requirements included in overall frame height**

100mm     150mm     190mm     No cill

*Note: 150mm Round Nose Cill as standard. Platform Height 20mm*

**Single Colours (both sides)**

RAL 9910 Hippca Gloss White  
 RAL 7016 Anthracite Matt Grey  
 RAL 9005 Matt Black

**Glazing**

28mm, Toughened, Low E, Argon Filled, Black Warm Edge Spacer

Glazed     Unglazed

*Note: 28mm Square Bead as standard.*

44mm Square Bead for Triple Glazing

**Handles**

White     Black     Chrome     Brushed Graphite

All windows are viewed from outside. All windows are shootbolt locking

Width \_\_\_\_\_ mm  
 Height \_\_\_\_\_ mm  
 Transom \_\_\_\_\_ mm  
 Mullion \_\_\_\_\_ mm  
 Quantity \_\_\_\_\_ mm  
 Trickle vent     Y     N  
 Fire egress     Y     N

Further info.

Width \_\_\_\_\_ mm  
 Height \_\_\_\_\_ mm  
 Transom \_\_\_\_\_ mm  
 Mullion \_\_\_\_\_ mm  
 Quantity \_\_\_\_\_ mm  
 Trickle vent     Y     N  
 Fire egress     Y     N

Further info.

Width \_\_\_\_\_ mm  
 Height \_\_\_\_\_ mm  
 Transom \_\_\_\_\_ mm  
 Mullion \_\_\_\_\_ mm  
 Quantity \_\_\_\_\_ mm  
 Trickle vent     Y     N  
 Fire egress     Y     N

Further info.

Width \_\_\_\_\_ mm  
 Height \_\_\_\_\_ mm  
 Transom \_\_\_\_\_ mm  
 Mullion \_\_\_\_\_ mm  
 Quantity \_\_\_\_\_ mm  
 Trickle vent     Y     N  
 Fire egress     Y     N

Further info.


*Note: Trickle Vents into a Deep Head Outerframe*

Features and Benefits


- Thermally Broken Super Slimline Aluminium Window System.
- Internally Beaded (Fixed Lights External)
- 28mm Double and 44mm Triple Glazed
- Fully Tested to PAS24:2012 Enhanced Security
- High Performance Polyamide Barrier giving U Values as low as 1.1
- Average U Values
- Residential CEN Standard 1230x1480
- 28mm Double Glazed Unit 1.5W/m2K

• Typical Sizes	Width mm	Height mm
Top Hung	1400	1400
Side Hung	950	1400
• Weather Rating BS6375 Part 1		
Air	600pa	
Water	600pa	
Wind	1600pa	


SPW700701  
Outerframe




SPW71617  
Deep Outerframe



SPW712713  
Flat Faced Vent



SPW706707  
Transom/Mullion  
(Screwport)



SPW730730  
25mm Add-on



SPW750753  
100mm Cill



SPW724  
Bead



SPW751753  
150mm Cill



SPW720  
Bead



SPW752753  
150mm Cill

